

[illegible]

FIG. 2




FIG. 4




FIG. 5




FIG. 6




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14





FIG. 15



16/106

FIG. 17




FIG. 18




FIG. 19




FIG. 20






FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34





FIG. 35





FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50





FIG. 51






FIG. 52

FIG. 53




FIG. 54





FIG. 55



(A)



FIG. 57

(A)

41Aa, 41Ba

14a

41Ac, 41Bc

41Ad

41Ac, 41Bc

(B)

30

12

39A

39Aa

39Ab

41A

41Aa

41Ab

41Abb

41Ac

41Ad

14a

24A

24Ab

11

20

(3) (2) (1) (0)

FIG. 58




FIG. 59




FIG. 60




FIG. 61





FIG. 62

FIG. 63




FIG. 64




FIG. 65







FIG. 66



(A)



(C)



(B)

FIG. 67




FIG. 68




FIG. 69




FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75

62




FIG. 76




FIG. 77




FIG. 78




FIG. 79






FIG. 80



(A)



(B)

FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86




FIG. 87




FIG. 88




FIG. 89




FIG. 90




FIG. 91




FIG. 92




FIG. 93




FIG. 94




FIG.95

FLOW OF OPERATION DURING DISK LOADING

	OPERATION CONTENT	WORKING MOTOR				
		M1	M2	M3	M4	M5
1	DRIVE CHASSIS UNIT IS MOVED INTO A POSITION PERMITTING THE SELECTION OF A HOLDER PLATE FOR STORING THE LOADED DISK		○			
2	DISK SELECTOR IS MOVED TO OPEN THE HOLDER PLATE TO A WIDTH PERMITTING THE INSERTION OF THE LOADING ROLLER (HOLDER OPEN POSIITON (1)).	○				
3	DRIVE CHASSIS UNIT IS RAISED TO A HEIGHT THAT ALLOWS DISK LOADING		○			
4	LOADING ROLLER IS MOVED TOWARD THE DISK HOLDER TO ENTER A STATE ALLOWING A DISK TO BE HELD	○				
	SHUTTER IS OPENED					
4	CATCHES OF DISK HOLD LINKS ARE CLOSED AND DISK HOLDER IS OPENED FURTHER SO THAT THE CENTER OF THE HOLDER PLATE DOES NOT OBSTRUCT THE DISK INSERTION PATH (HOLDER OPEN POSITION (2)).					
5	DISK IS DETECTED BY SENSOR AND LOADING ROLLER IS ROTATED IN THE LOADING DIRECTION (FORWARD DIRECTION)			○		
6	THE COMPLETE STORAGE OF THE DISK IN THE DISK HOLDER IS DETECTED AND ROTATION OF THE LOADING ROLLER IS STOPPED					
7	SHUTTER IS CLOSED AND DISK IS HELD ON HOLDER PLATE	○				
8	DRIVE CHASSIS UNIT IS MOVED SO THAT THE HOLDER PLATE IS AT THE HEIGHT OF THE INITIAL POSITION		○			
9	LOADING ROLLER AND DISK STOPPER ARE REMOVED FROM DISK	○				
	DISK SELECTOR IS REMOVED FROM HOLDER PLATE TO ESTABLISH A STATE WHERE THE HOLDER PLATE IS BONDED					
11	DRIVE CHASSIS UNIT MOVES TO HEIGHT OF INITIAL POSITION		○			

FIG. 96

FLOW OF OPERATION DURING DISK PLAYBACK

	OPERATION CONTENT	WORKING MOTOR				
		M1	M2	M3	M4	M5
1	DRIVE CHASSIS UNIT IS MOVED INTO A POSITION PERMITTING THE SELECTION OF A HOLDER PLATE FOR STORING THE DISK TO BE PLAYED BACK		○			
2	DISK SELECTOR IS MOVED TO OPEN THE HOLDER PLATE TO A WIDTH PERMITTING THE INSERTION OF THE LOADING ROLLER (HOLDER OPEN POSITION (1)).	○				
	LOADING ROLLER AND DISK STOPPER ARE MOVED TO HOLD DISK					
	CATCHES OF DISK HOLD LINKS ARE CLOSED AND DISK IS REMOVED BY OPENING THE DISK HOLDER FURTHER (HOLDER OPEN POSITION (2)).					
	DISK HOLDER IS OPENED FURTHER (HOLDER OPEN POSITION (3)) TO INTRODUCE DRIVE BASE					
	TURNTABLE IS INTRODUCED BELOW DISK BY ROTATING THE DRIVE BASE					
	CLAMPER RING IS CLOSED WHILE LIFTING UP DRIVE UNIT AND DISK IS CHUCKED ON TURNTABLE					
	LOADING ROLLER AND DISK STOPPER ARE MOVED TO A POSITION OF NON-CONTACT WITH THE DISK					
	FLOATING BLOCK IS RELEASED TO PUT DRIVE UNIT IN FLOATING STATE					
3	PICKUP IS FED TO INNER CIRCUMFERENCE BY THREAD MOTOR				○	
4	DISK IS PLAYED BACK THROUGH ROTATION					○

FIG. 97




FIG. 98




FIG. 99




FIG. 100







FIG. 101










FIG. 104




FIG. 106

